

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61B 17/17	A1	(11) International Publication Number: WO 00/25681 (43) International Publication Date: 11 May 2000 (11.05.00)
(21) International Application Number: PCT/GB99/03601 (22) International Filing Date: 2 November 1999 (02.11.99) (30) Priority Data: 9823974.2 2 November 1998 (02.11.98) GB (71) Applicant (for all designated States except US): GRAMPIAN HEALTHCARE NATIONAL HEALTH SERVICE TRUST [GB/GB]; Foresterhill, Aberdeen AB25 2ZN (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): WARDLAW, Douglas [GB/GB]; Mill of Monquich, Netherley, Stonehaven AB39 3QR (GB). (74) Agents: STEBBING, Peter, John, Hunter et al.; Ablett & Stebbing, Caparo House, 101-103 Baker Street, London W1M 1FD (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: FRACTURE TREATMENT		
(57) Abstract		
<p>The invention provides apparatus for the treatment of a bone fracture (18'), comprising an elongate member (2) adapted for substantially axial insertion into the bone (18) such that it spans the fracture; where in one embodiment the elongate member being formed, adjacent one or both of its proximal and distal ends with fixture location means (9) adapted to receive a fixing device (27) inserted transversely of the elongate member (2) and passing through part at least of the bone to be treated; the position of the fixture location means (9) and the line of insertion of the fixing device (27) being defined by a jig (21) temporarily affixable to the proximal end of the elongate member; wherein a guide means (25) is adapted to pass through the fixture location and act as a guide for the desired location of the fixing device, said apparatus also providing drill means (25a and 26a), guidable by the guide means, and utilizable to form a bore communicating with the fixture location and adapted to accommodate the fixing device.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

- 1 -

FRACTURE TREATMENT

This invention relates to the treatment of fractures, and it relates especially, though not exclusively, to apparatus for
5 effecting such treatments as are applicable to fractures of long bones such as the humerus.

A well established and highly successful procedure used in the treatment of long bone fractures involves the use of
10 intramedullary nails which are inserted substantially axially of a bone and to one side of the fracture, and extend through the medullary cavity (reamed out if necessary) and past the region of fracture to an area of sound bone. The proximal end of such a nail is secured to the bone at or adjacent to
15 the region of its entry into the bone, whereas the distal end of the nail has to be secured to the sound bone beyond the fracture. One difficulty associated with this procedure is the accurate location of the nail and its fixing points with which separate securing members, such as transversely
20 inserted fixing devices, e.g. screws, need to engage.

It has previously been proposed to use radiographic techniques to assist the surgeon in this respect, but it is preferable to avoid subjecting a patient to radiation for
25 such purposes, and accordingly various mechanical procedures have been developed in recent years. Such procedures typically involve the use of jigs which are attachable to the nail during the surgical alignment process and which provide predictive guidance as to the location of the nail
30 (particularly the distal end thereof), thereby to ease the difficulty described above.

Alignment procedures of this general kind are described in GB

- 2 -

2 288 738 A; GB 2 258 154 A; WO 96/03085 A1; US 5 352 228 and
US 4 913 137 and it is an object of this invention to provide
improved apparatus and methods for the application, alignment
and/or engagement of transverse fixing devices with
5 intramedullary nails, and/or to effect improved stability
and/or mobility of fractured bones.

According to the invention in one aspect there is provided an
apparatus for the treatment of bone fracture, comprising an
10 elongate member for substantially axial insertion into the
bone such that it spans the fracture; the elongate member
being formed, adjacent one or both of its proximal and distal
ends with a fixture location means, which may comprise an
aperture which is intended to receive a fixing device
15 inserted transversely of the elongate member and passing
through part at least of the bone to be treated; the position
of the fixture location and the line of insertion of the
fixing device being defined by a jig temporarily affixed to
the proximal end of the elongate member; characterised in
20 that a guide means is passed through the fixture location and
acts as a guide for the desired location of the fixing
device, and drill means guided by the guide means, is used to
form a bore communicating with the fixture location, said
bore being adapted to accommodate the fixing device.

25

Preferably the guide means comprises a wire, such as a K-
wire, and the drill means is axially apertured to accommodate
said wire.

30 According to another aspect of the invention there is
provided an apparatus for the treatment of bone fracture,
comprising an elongate member for substantially axial
insertion into the bone such that it spans the fracture, the

- 3 -

elongate member being formed, adjacent at least its distal end with a fixture location intended to receive a fixing device inserted transversely of the elongate member and to engage with an aperture present in the elongate member so as to permit the elongate member to be drawn into intimate contact with the inner surface of cortical bone, thereby to enable the elongate member to act as a support member.

Preferably the fixing device is a screw and the fixture location comprises an internally threaded aperture formed in said elongate member.

Preferably the elongate member is formed with a plurality of further apertures adjacent the distal end thereof, any or all of which further apertures may be internally threaded.

Preferably, the elongate member comprises an intramedullary nail configured in the region thereof occupied by said aperture and possibly also said further apertures to permit its close conformity to the inner cortical wall of said bone.

Preferably also the proximal end of said elongate member also is formed with one or more apertures to accommodate transversely disposed fixing devices.

25

Where a plurality of said fixing devices is employed to cooperate with respective apertures adjacent the proximal end of said elongate member, said fixing devices are adapted to pass through the elongate member and into sound bone and are deployed in substantially parallel planes transverse to said elongate member, but are misaligned so as to respectively engage areas of bone more widely separated than the areas that would have been engaged by the fixing devices had they

30

- 4 -

been disposed in alignment with one another.

In an alternative embodiment, an elongate member is adapted to be passed through a fixing device whereafter the fixing
5 location of the proximal end of said elongate member resides in contact with the fixing device.

Conveniently, the said fixing device may comprise an aperture whereby said elongate member can pass through the fixing
10 device in use.

According to a further aspect of the invention there is provided a method for the treatment of bone fracture, comprising the steps of:-

15 inserting an elongate member formed adjacent one or both of its proximal and distal ends with a fixture location, said elongate member being insertable substantially axially into the bone such that it spans the fracture; the fixture location being adapted to receive a fixing device inserted
20 transversely of the elongate member and passing through part at least of the bone to be treated;

defining, by means of a jig temporarily affixed to the proximal end of the elongate member, the position of the fixture location and the line of insertion of the fixing
25 device;

utilising said jig to pass a guide means through the fixture location and along said line of insertion;

anchoring said guide means into sound bone; and

drilling, guided by the guide means, a bore
30 communicating with the fixture location and adapted to accommodate the fixing device.

According to a still further aspect of the invention there is

- 5 -

provided a method for the treatment of bone fracture, comprising the steps of:

forming adjacent at least the distal end of an elongate member, with a fixture location adapted to receive a fixing device inserted transversely of the elongate member and to engage with the aperture of the elongate member and inserting said elongate member substantially axially into the bone such that it spans the fracture; and

utilising the fixing device in cooperation with the fixture location formed in the elongate member to draw the elongate member into intimate contact with said bone.

A particular application of the invention relates to the treatment of four-part and other fractures of the surgical neck and shaft of the humerus.

Comminuted four-part fractures of the upper end of the humerus present particular difficulties in imparting a sufficient degree of stability to the repaired bone structure. In attempting to stabilise the structure, it is necessary to take into account the forces acting on the fracture fragments, such as the supraspinatus muscle and the other muscles of the rotator cuff which act on the main proximal fragment of the fracture through the greater and lesser tuberosities. Sometimes, moreover, the greater tuberosity is a separate fragment and is displaced by muscular pull. The lesser tuberosity may also be a separate fragment, which tends to follow the greater tuberosity fragment because of the close attachment of the rotator cuff muscles.

Secure fixing of the distal end of an intramedullary nail enables the latter to be used as an internal plate,

- 6 -

stabilising the repaired structure.

In order that the invention may be clearly understood and readily carried into effect, one embodiment thereof will now
5 be described, by way of example only, with reference to the accompanying drawings, of which:

Figure 1(a) shows a cross section of the proximal end of the patient's humerus from above with an elongate member 2
10 inserted axially throughout and 1(b) shows a similar view through the distal end of the humerus and elongate member 2. Figures 1(c) and 1(d) show respectively antero-posterior cross sectional and side views of the elongate member 2, with a plurality of holes therethrough;

15

Figure 2 shows a side view of the patients fractured humerus positioned prior to surgical procedure;

Figure 3 shows a side view of a trocar positioned prior to
20 reaming a channel for an intramedullary nail;

Figure 4 shows a side view of the nail in position in the proximal humerus, with a jig removably attached to the nail;

25 Figure 5 shows a side view similar to that of Figure 4 and indicates the use of the jig to position the insertion of cannulate trocars into a cancellate region of the humeral head;

30 Figure 6 shows a side view indicating the line of insertion of so-called K-wires axially of the trocars and into the subchondral bone of the humeral head;

- 7 -

Figure 7 shows a side view similar to that shown in Figures 4 to 6 involving the use of centrally apertured drills inserted (following removal of the trocars) axially over the K-wires, using the latter as guides, to drill the lateral 5 cortex to respectively receive proximal fixing screws;

Figure 8 shows a side view similar to that shown in Figures 4 to 7 and indicates the insertion of screws over the K-wires;

10

Figure 9 shows a side view similar to that shown in Figure 6 indicating the removal of K-wires from the humeral head;

Figure 10 shows a side view indicating the line of insertion 15 of K-wires axially of the trocars and into the cortical bone of the humeral shaft;

Figure 11 shows a side view where at the distal end of the humeral shaft a cannulated drill is passed over a K-wire;

20

Figure 12 shows a side view of insertion of a cannulated screw into the central position of the distal end of the nail.

25 Figure 13 shows a side view of the humeral shaft where the proximal and distal screws have been inserted into the bone and through the intramedullary nail.

Figure 14 shows a side view of the nail in position in the 30 proximal humerus, with a jig removably attached to the nail to aid insertion of two K-wires and to aid insertion of a guide wire through a drill guide into the subchondral bone of the humeral head

- 8 -

Figure 15 shows a side view of the guide demonstrating the positioning of the K-wires;

Figure 16 shows the insertion of a drill bit along the guide 5 wire, guided by the jig which is removably attached to a "short" nail.

Figure 17 shows a "flanged" bolt inserted along the guide wire;

10

Figure 18 shows insertion of an intramedullary nail through the aperture of the "flanged" bolt;

Figure 19 shows a side view of the humeral shaft where the 15 intramedullary nail has been inserted through the "flanged" bolt and secured at the distal end by screws. A locking grub screw is inserted into the "flanged" bolt and a toothed washer may also be inserted to stabilise Tuberosity fracture fragments.

20

25 Referring now to Figure 1(a), the patient's humerus from above is shown at 1, with the proximal end of an elongate member, in this instance an intramedullary fixing nail, indicated at 2. First and second proximal fixing devices, in this case screws 3 and 4, are provided, as will be described 30 more fully hereinafter. These screws pass, transversely of the nail 2, through respective holes in the shank thereof, into the sound bone of the humeral head, thereby creating a stable structure fixing the humeral head to the humeral

- 9 -

shaft. It is preferable, though not essential, that the screws 3 and 4 are inserted through the nail 2 at different angles, though in substantially parallel planes, in order that they may engage portions of the humeral head that are 5 relatively well separated from one another. This expedient assists in creating a structure stably fixing the humeral head to its shaft, though clearly the profile of the nail itself and the profile and/or dimensions of the respective holes therein through which the screws 3 and 4 pass must be 10 formed so as to accommodate the splayed insertion of the screws.

Typically in this respect, the proximal portion 5 of the nail 2 is round or ovoid or rectangular in cross-section whereas 15 the remainder of the nail 6 is ovoid or a curved oblong or rectangular, or otherwise conforms to a generally flattened cross-section, to enable it to be used as an internal plate, whereby, as shown in Figure 1(b), the distal end of the nail may be drawn, by means of one or more lateral fixing screws 20 7, intimately against the internal surface of the humeral shaft 8.

Figures 1(c) and 1(d) show respectively antero-posterior cross sectional and side views of the nail 2, with a 25 plurality of holes therethrough. Holes 9 and 10 are adjacent the proximal end of the nail and holes 11, 12 and 13 near the distal end thereof; at least the hole 12, but preferably all three being internally screw-threaded in order to permit the use of the nail 2 as a supportive plate, as illustrated in 30 Figure 1(b). The plates may contain any number of holes greater than 3 if necessary.

With reference now to Figure 2, the humeral head and shaft

- 10 -

are shown at 1 and 8 respectively, together with certain adjacent anatomical features such as the acromion process 14, the deltoid muscle 15, the greater tuberosity 16 and the glenoid 17. The surgical neck is indicated at 18 and the bone fracture is indicated at 18'.

The line of surgical approach is shown by arrow 19, splitting the deltoid muscle 15 to reach the point of insertion of the nail 2

10

A trocar 20 is inserted, as shown in Figure 3, close to the point at which the nail 2 is to be inserted, through a small incision just lateral to the acromion 14, so that it passes close to the lateral cortex. If this should prove difficult, for example because the humeral head is in abduction, the insertion of a bone awl or external fixator screw on an introducer into the humeral head (proximal fragment) will allow it to be manipulated into an appropriate position.

20 An antero-lateral approach to the shoulder may be used in addition, if the fracture proves difficult to reduce.

As shown in Figure 4, a jig 21 is removably attached to the top of the nail 2 before introduction, to guide its insertion. The jig 21 is constructed and dimensioned so as to act as a guide for the insertion of transverse locking/location screws such as 3 and 4 at the proximal end and others at the distal end as previously outlined and as to be described in more detail hereinafter. Jig 21 engages a slot in the top of the nail 2 and is removably fixed in position by means of a screw 22 engaging an internal screw thread formed, in known manner, axially in the top end of the nail 2. The cortical bone of the humeral shaft in cross-

- 11 -

section is represented at 8'.

In order to securely affix the proximal end of the nail 2 to the humeral head, the procedure illustrated in Figures 5 to 9 is followed. Using holes in the jig 21 designed to align with the holes 9 and 10 in the nail 2 (Figure 1), for alignment, drill holes are made in the bone which ultimately define the positions of proximal screws in the cancellous bone of the humeral head. Trocars 23 and 24, with tissue protectors shown at 23a and 23b in Figure 7, are first introduced through a small skin puncture. K-wires 25 and 26 are then passed axially down the trocars 23, and 24 and securely anchored into the subchondral bone of the femoral head. A principal purpose of the wires is to serve as guides for a subsequently performed drilling procedure. The trocars are next removed and a drill which is axially apertured to accommodate a wire, inserted over each of the K-wires in turn (as indicated at 25a and 26a in Figure 7) to drill into the lateral cortex in spaced-apart positions as described with reference to Figure 1(a). Such a drill will hereinafter be referred to as a cannulated drill; the intention being that it is accurately guided by the K-wire passing centrally through it.

A measuring device is then used to measure the required screw length, and cannulated (axially apertured) cancellous screws 27 and 28 of length chosen to terminate 5mm short of the subchondral bone of the humeral head are then passed over the K-wires, which later are then removed, leaving the screws 27 and 28 in position.

The screws to engage with the distal end of the nail 2 are inserted similarly, according to the sequence illustrated in

- 12 -

Figures 10 to 13.

As at the proximal end of the nail 2, trocars 29, 30 and 31 with tissue protectors are inserted down to the bone, and 5 respective K-wires 32, 33 and 34 passed therethrough to securely anchor in the opposite (medial) cortex through the respective holes 11, 12 and 13 (Figure 1) in the nail 2. The middle hole of the three 12 is preferably drilled first, using a cannulated drill (indicated at 33a in Figure 11) as 10 before, guided by the K-wire 33 which passes axially through it. A cannulated screw 35, long enough to engage only the threaded hole 12 in the nail, is then inserted and screwed up, drawing the nail into intimate contact with the inner cortex so that it acts as an internal plate and thereby 15 providing increased stability of the repair. The screw head should be large or preferably of normal size or with a washer large enough to spread the load to prevent the screw breaking out of what may be relatively osteoporotic bone in an elderly person. A second screw may be inserted in the same way to 20 create even firmer contact between the nail 2 and the bone, and the other cannulated self-tapping screws 36, 37 are then likewise inserted, though these are of length sufficient to ensure gripping both of the respective screw threads formed in the holes 11 and 13 through the nail and of the medial 25 cortex.

The jig 21 has then served its purpose and is removed; the axial screw-thread at the proximal end of the nail 2 thus vacated receiving instead a screw-in top 38 (Figure 13) that 30 holds a washer 39 which may be apertured (39a) and/or formed with radially extending claws (39b). The rotator cuff muscles may be stitched to the washer and/or attached to the nail via the aforesaid claws to transmit force through the

- 13 -

nail 2 to the humeral shaft, creating a stable structure. Other fracture fragments may be attached by means of interfragmentary screws or circlage wires.

5 In an alternative embodiment as shown in Figures 14-19, the insertion of two locking/location screws such as 3 and 4 may be substituted by the insertion of one "flanged" bolt 47 (Figures 17 to 19).

10 The steps previously demonstrated in Figures 5 to 9, may be substituted with the following. An intramedullary nail 2 is inserted into the humeral head whilst removably attached to a jig 21. A drill guide 41 is then used to aid the placement of a guide wire 42 through the humeral head 1 whereby the
15 guide wire is passed axially down the drill guide and is securely anchored into the subchondral bone of the humeral head (See Figure 14). The jig allows accurate positioning of the guide wire. The preliminary intramedullary nail 2 is slotted into the coronal plane in such a manner as to permit
20 its removal without displacing the affixed guide wire 42. The jig 21 contains a telescopic section to permit insertion and withdrawal of the nail 2.

The jig 21 also aids accurate positioning of the two K-wires
25 43 and 44 (See Figure 15). The function of the K-wires is to maintain the fracture position until a final nail 2' (See Figure 18), which is to remain implanted in the bone (in the coronal plane) throughout treatment, is inserted into the bone.

30

Prior to insertion of the final nail 2', the preliminary intramedullary nail 2 is replaced by a "short" intermediate nail 46 as shown in Figure 16. The "short" nail is inserted

- 14 -

into the tuberosity in the coronal plane to provide additional stability to the K-wires whilst the humeral head is prepared for the "flanged" bolt 47.

5 A cannulated drill bit 45 is placed over the free end of the guide wire 42 (See Figure 16) and is moved along the wire to drill into the bone. Once drilling is completed the drill bit 45 is removed and a cannulated "flanged" bolt 47 is inserted into the drilled hole along the guide wire 42 (See
10 Figure 17) running throughout the cannulated bolt. The "short" preliminary nail 46 is still in place and continues to provide stability while the "flanged" bolt is being inserted. The "flanged" bolt 47 comprises an insertion section 60 and an extension section 61. The extension
15 section 61 is removably attached to the insertion section by way of a threaded locking pin 62.

Once the "flanged" bolt has been inserted, the "short" intermediate nail 46 is removed and the final intramedullary
20 nail 2' inserted through an aperture 40 provided in the "flanged" bolt 47. The guide wire 42 and K-wires 43 and 44 can then be removed (See Figure 18).

When the final intramedullary nail 2' has been safely located
25 in position through the bolt 47, the bolt extension 61 and jig 21 can be removed. The final nail 2' and bolt 47 are locked together by insertion of a grub screw 49 which thereby stabilizes the structure, locking the final nail 2' (See Figure 19). A toothed washer 50 may be inserted to enhance
30 stability of tuberosity fracture fragments. Screws such as 35, 36 and 37 are inserted as before (See Figures 10 to 13) in the distal portion of the final nail 2' to secure the implant to the distal fracture fragments.

- 15 -

It will be appreciated by those skilled in the art that relatively longer nails can be used to provide fixation of fractures of the shaft of the bone. It will also be appreciated that such a nail can be adapted for use in any 5 bone throughout the body.

- 16 -

CLAIMS.

1. Apparatus for the treatment of a bone fracture,
comprising an elongate member adapted for substantially
axial insertion into the bone such that it spans the
fracture; the elongate member being formed, adjacent one
or both of its proximal and distal ends with fixture
location means adapted to receive a fixing device
inserted transversely of the elongate member and passing
through part at least of the bone to be treated; the
position of the fixture location means and the line of
insertion of the fixing device being defined by a jig
temporarily affixable to the proximal end of the
elongate member; wherein a guide means is adapted to
pass through the fixture location and act as a guide for
the desired location of the fixing device, and drill
means, guidable by the guide means, and utilizable to
form a bore communicating with the fixture location and
adapted to accommodate the fixing device.
2. Apparatus according to claim 1 wherein the guide means
comprises a wire and the drill means is axially
apertured to accommodate said wire.
3. Apparatus according to claim 2 wherein the guide means
comprises a K-wire.
4. Apparatus wherein the fixing device is adapted to be
inserted transversely of the elongate member and to
engage with the aperture so as to permit the elongate
member to be drawn into intimate contact with the inner
surface of cortical bone, thereby enabling the elongate
member to act as a support member.

- 17 -

5. Apparatus according to any proceeding claim wherein the elongate member is formed with a plurality of further apertures adjacent the distal end thereof.
- 5 6. Apparatus according to claim 5 wherein at least one of said further apertures is internally threaded.
7. Apparatus according to any proceeding claim wherein the elongate member is in the form of an intramedullary nail
10 and is configured, in the region of its distal end, to permit close conformity to an inner wall of said bone.
8. Apparatus according to any preceding claim wherein the fixing device is a screw and the fixture location means
15 comprises an internally threaded aperture formed in said elongate member.
9. Apparatus according to any preceding claim wherein the proximal end of said elongate member is formed with one
20 or more apertures to accommodate transversely disposed fixing devices.
10. Apparatus according to claim 9 wherein a plurality of said fixing devices are adapted to cooperate with
25 respective apertures adjacent the proximal end of said elongate member, said fixing devices being adapted to pass through the elongate member and into sound bone and being deployable in substantially parallel planes transverse to said elongate member, but axially
30 misaligned so as to respectively engage areas of bone more widely separated than the areas that would have been engaged by the fixing devices had they been disposed in axial alignment with one another.

- 18 -

11. Apparatus according to claims 1 to 4 wherein an elongate member is adapted to be passed through a fixing device whereafter the fixing location of the proximal end of said elongate member resides in contact with the fixing device.
12. Apparatus according to claim 11 wherein said fixing device comprises an aperture whereby said elongate member can pass through the fixing device in use.
13. Apparatus according to any preceding claim wherein a jig is adapted to be removably secured to the proximal end of said elongate member to aid in the positioning of said fixing devices relative to said elongate member.
14. A method for the treatment of a bone fracture, comprising the steps of:-
- inserting an elongate member formed adjacent one or both of its proximal and distal ends with a fixture location means, said elongate member being insertable substantially axially into the bone such that it spans the fracture; the fixture location means being adapted to receive a fixing device inserted transversely of the elongate member and passing through part at least of the bone to be treated;
- defining, by means of a jig temporarily affixed to the proximal end of the elongate member, the position of the fixture location and the line of insertion of the fixing device;
- utilising said jig to pass a guide means through the fixture location and along said line of insertion;
- anchoring said guide means into sound bone; and
- drilling, guided by the guide means, a bore communicating with the fixture location and adapted to

- 19 -

accommodate the fixing device.

15. A method according to claim 14 which comprises utilising the fixing device in cooperation with the fixture location
5 means formed in the elongate member to draw the elongate member into intimate contact with said bone.
16. A method according to claim 14 wherein said elongate member comprises an intramedullary nail apertured at
10 said fixture location and said fixing means comprises a screw passing through and/or engaging within said aperture.
17. A method according to any of claims 14 to 16 including
15 the further step of drilling a bore to accommodate said fixing device using an axially apertured drill.

1/9

FIG. 1(a)





FIG. 1(b)




FIG. 1(c)




FIG. 1(d)

2/9




FIG. 2






FIG. 3

3/9



4/9




FIG. 6






FIG. 7

5/9



6/9




FIG. 10




FIG. 11

7/9




FIG. 12








FIG. 13

8/9



9/9



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/03601

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B17/17

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 374 271 A (HWANG) 20 December 1994 (1994-12-20) the whole document ---	1-13
Y	US 4 522 201 A (TONGUE) 11 June 1985 (1985-06-11) abstract; figures 5-9 column 6, line 1-42 column 6, line 62 -column 7, line 7 ---	1-13
A	WO 92 01422 A (NATIONAL RESEARCH DEVELOPMENT CORPORATION) 6 February 1992 (1992-02-06) abstract; figures page 9, line 17 -page 10, line 1 --- -/--	1,4-13

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

3 February 2000

Date of mailing of the international search report

11/02/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Giménez Burgos, R

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/03601

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 92 06 580 U (HOWMWDICA INTERNATIONAL INC.) 23 July 1992 (1992-07-23) page 9, line 10 -page 11, line 3; figures ----	1-3, 10-13
A	BE 678 171 A (DESCAMPS) 1 September 1966 (1966-09-01) figures 1-7 -----	1-3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/GB 99/03601

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 14-17
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03601

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5374271 A	20-12-1994	DE 4414177 A DE 9406779 U FR 2719212 A GB 2288738 A, B JP 2551736 B JP 7299079 A	26-10-1995 16-06-1994 03-11-1995 01-11-1995 06-11-1996 14-11-1995
US 4522201 A	11-06-1985	NONE	
WO 9201422 A	06-02-1992	EP 0493570 A JP 5501666 T	08-07-1992 02-04-1993
DE 9206580 U	23-07-1992	AT 139100 T AU 647619 B AU 1620292 A CA 2068139 A DE 69211429 D DE 69211429 T EP 0521600 A ES 2088100 T IE 79046 B JP 5176942 A US 5454813 A	15-06-1996 24-03-1994 07-01-1993 25-12-1992 18-07-1996 24-10-1996 07-01-1993 01-08-1996 08-04-1998 20-07-1993 03-10-1995
BE 678171 A	01-09-1966	CH 441611 A	15-01-1968